



ORDERING INFORMATION

PART NUMBER	DESCRIPTION
INSTRUMENT CONFIGURATIONS	
TX1-1	Tango TX1, CO
TX1-2	Tango TX1, H ₂ S
TX1-4	Tango TX1, NO ₂
TX1-5	Tango TX1, SO ₂
ACCESSORIES	
18109201	iNet DS docking station for Tango*
17154367	Replacement battery
18109171	Soft nylon case, Black
18109239	Soft nylon case, Orange
18109218	Dust barrier kit, 5 pack
18109230	Water barrier kit, 5 pack
18109238	CalCup and tubing kit
17120908	Belt clip
17154915-0	AlarmAmp™, Black
17154915-1	AlarmAmp™, Safety Orange
17154916	Black nameplate
17154917	Green nameplate
17154918	Yellow nameplate
17154919	Blue nameplate
17154920	White nameplate

*Access to data from the iNet DS docking station requires a subscription to iNet or iNet InSite.

SPECIFICATIONS

INSTRUMENT WARRANTY:

Three year warranty which does not include battery, sensors and filters.
CO and H₂S sensors are warranted for 3 years from the initial purchase date.
All other sensors are warranted for 2 years from the initial purchase date.

DISPLAY:

Segment liquid crystal display (LCD)

KEYPAD:

Two buttons

CASE MATERIALS:

Case top: Polycarbonate with a protective rubber overmold
Case bottom: Conductive polycarbonate

ALARMS:

Three strobe-emitting visual alarm LEDs (two red; one blue);
100 decibel (dB) audible alarm at a distance of 10 cm (3.94"); Vibration alarm

DIMENSIONS:

99 x 51 x 35 mm (3.9" x 2.0" x 1.4")

WEIGHT:

126.0 g (4.4 oz.)

OPERATING TEMPERATURE RANGE:

-20°C to +50°C (-4°F to +122°F)

OPERATING HUMIDITY RANGE:

15%-95% Non-condensing (continuous)

INGRESS PROTECTION:

IP66; IP67

SENSORS:

CO, H₂S, NO₂, SO₂ - Electrochemical sensor technology

SENSOR MEASURING RANGES:

Carbon Monoxide (CO): 0.0 to 1,000.0 ppm in 1.0 ppm increments
Hydrogen Sulfide (H₂S): 0.0 to 200.0 ppm in 0.1 ppm increments
Nitrogen Dioxide (NO₂): 0.0 to 150.0 ppm in 0.1 ppm increments
Sulfur Dioxide (SO₂): 0.0 to 150.0 ppm in 0.1 ppm increments

BATTERY PACK:

3.6 V Primary lithium-thionyl chloride (Li-SOCl₂), 1.5AH, 2/3AA, replaceable, nonrechargeable

CERTIFICATIONS:

ATEX Ex ia I Ma
Ex ia IIC T4 Ga
Equipment Group and Category: I M1 and II 1G
IECEX Ex ia I Ma
Ex ia IIC T4 Ga
UL (C-US) Class I, Groups A, B, C, and D; Class II, Groups E, F, and G; T4; Exia Class I, Zone 0, AEx ia IIC T4

PENDING:

CSA Ex ia IIC T4
MSHA Permissible Gas Monitor
INMETRO Ex ia IIC T4; Zone 0

These specifications are based on performance averages and may vary by instrument.

*The Tango is warranted to be free from defects in material and workmanship under normal and proper use and service for 3 years from the initial purchase date.

INDUSTRIAL SCIENTIFIC

www.indsci.com

AMERICAS

Phone: +1-412-788-4353
1-800-DETECTS (338-3287) North America
Fax: +1-412-788-8353
info@indsci.com

ASIA PACIFIC

Phone: +65-6561-7377
Fax: +65-6561-7787
info@ap.indsci.com

EUROPE

Phone: +33-3-21-60-80-80
00-800-WORKSAFE (9675-7233) Europe
Fax: +33-3-21-60-80-00
customersupport@eu.indsci.com